

# PORCELAIN WOOD

Unrivaled strength. Timeless beauty.



## Dalby Silk

A range of minimal, lime-washed wood grains that echo the aesthetic of a beach-side boardwalk, manufactured with a desirably smooth and silky finish

Product displayed is Dalby Silk Hazelnut

# PORCELAIN WOOD

Unrivalled strength. Timeless beauty.

## The Dalby Silk Range



Dalby Silk Light



Dalby Silk Hazlenut



Dalby Silk Ash





Dalby Silk Coast



Dalby Silk Natural

Dimensions: 14.4 x 89.3cm (5.7 x 35.2 inches)

  11.5mm thickness

---



Dalby Silk Light



Dalby Silk Hazlenut



Dalby Silk Ash





Dalby Silk Coast



Dalby Silk Natural

Dimensions: 21.8 x 89.3cm (8.6 x 35.2 inches)

  11.5mm thickness

---

# PORCELAIN WOOD

Unrivaled strength. Timeless beauty.

Technical characteristics		Reference standard
Manufacture process	Single-firing	Dry pressed ceramic tile
Thickness (mm)	11.5	UNE EN ISO 10545 Part 2
Length, width, thickness, side straightness, orthogonality, flatness	Conforms to the requisites applicable to each model as defined in standard UNE-EN 14411 for Group B la	UNE EN ISO 10545 Part 2
Water absorption	E< 0.5 %	UNE EN ISO 10545 Part 3
Flexion resistance N/sq. mm. and breaking strength	> 35 > 1300	UNE EN ISO 10545 Part 4
Resistance to surface abrasion (Glazed tiles)	Available on request	UNE EN ISO 10545 Part 7
Lineal thermic dilatation	< 9*10 <sup>-6</sup> /° C	UNE EN ISO 10545 Part 8
Thermic impact resistance	Conforms to industrial standard	UNE EN ISO 10545 Part 9
Cracking resistance	Conforms to industrial standard	UNE EN ISO 10545 Part 11
Frost resistance	Conforms to industrial standard	UNE EN ISO 10545 Part 12
Slip resistance	Class 1	UNE ENV 12633:2003

Chemical resistance		
Domestic cleaning products	Type GA	UNE EN ISO 10545 Part 13
Swimming pool salt	Type GA	
Acids and bases (low concentration)	Minimum Type GLB	UNE EN ISO 10545 Part 14
Stains resistance	Minimum Type 4	


## Matching With Our Dalby Textured Range

Our Dalby range is unique in our portfolio of products, as it is available in two different finishes; Textured (for a hand-scraped, anti-slip finish) and Silk (offering a smoother and slightly glossier feel). These two ranges can be combined to maintain a consistent appearance across areas that have different requirements. This would allow the running of the same tile inside your house in the Silk finish, through to an exterior balcony or patio in the Textured, anti-slip finish. This is also ideal for bathroom or wetroom areas, where Textured tiles can be applied to the floor, complimented with a Silk finish on the walls.


cut and bevelled skirting tile  
9.4 x 44.3 cm / 3.7 x 17.4 inches  
Dalby Silk-CR



staircase step  
44.3 x 89.3 cm / 17.4 x 35.2 inches  
Dalby Silk-CR



step lip  
44.3 x 89.3 cm / 17.4 x 35.2 inches  
Dalby Silk-CR



The staircase step and gradone can be sold with or without the ribbed notch. Angle is also available.