

PORCELAIN WOOD

Unrivaled strength. Timeless beauty.



Rutland

A range of distressed wood grains with a vivid Mediterranean colour pallet inspired by reclaimed panels from disused Spanish fishing boats

Product displayed is Rutland Earth

PORCELAIN WOOD

Unrivaled strength. Timeless beauty.

The Rutland Range



Rutland Ash



Rutland Earth



Rutland Sky



Rutland Ocean



Rutland Volcano



Rutland Amber

Dimensions: 14.4 x 89.3cm (5.7 x 35.2 inches)



10mm thickness

Technical characteristics		Reference standard
Manufacture process	Single-firing	Dry pressed ceramic tile
Thickness (mm)	10	UNE EN ISO 10545 Part 2
Length, width, thickness, side straightness, orthogonality, flatness	Conforms to the requisites applicable to each model as defined in standard UNE-EN 14411 for Group B Ia	UNE EN ISO 10545 Part 2
Water absorption	E < 0.5 %	UNE EN ISO 10545 Part 3
Flexion resistance N/sq. mm. and breaking strength	> 35 > 1300	UNE EN ISO 10545 Part 4
Resistance to surface abrasion (Glazed tiles)	Available on request	UNE EN ISO 10545 Part 7
Lineal thermic dilatation	< 9*10 ⁻⁶ /° C	UNE EN ISO 10545 Part 8
Thermic impact resistance	Conforms to industrial standard	UNE EN ISO 10545 Part 9
Cracking resistance	Conforms to industrial standard	UNE EN ISO 10545 Part 11
Frost resistance	Conforms to industrial standard	UNE EN ISO 10545 Part 12
Slip resistance	Class 1 R9	UNE ENV 12633:2003
Chemical resistance		
Domestic cleaning products	Type GA	UNE EN ISO 10545 Part 13
Swimming pool salt	Type GA	
Acids and bases (low concentration)	Minimum Type GLB	
Stains resistance	Minimum Type 4	

anti-slip  R9

DEDICATED SLIP RESISTANCE. The Rutland range is specifically designed to provide better safety in areas of pedestrian traffic, where the humidity conditions and slopes are greater than normal. Rutland rates higher than the test results recommended by Regulation UNE-ENV 12633:2003.

cut and bevelled skirting tile
9.4 x 44.3 cm / 3.7 x 17.4 inches
Rutland-R



T: +44 (0) 844 854 3050 E: ask@porcelainwood.com W: www.porcelainwood.com